

7390

- Shell mill arbor
- Balanced @G2.5/25,000 RPM
- Coolant-thru



Code No.	K PSC Taper	d [in]	A [in]	L [in]	d1 [in]
7-148-360	32	3/4	1.75	0.68	1.75
7-148-460	40	3/4	2.00	0.68	1.75
7-148-480	40	1	2.00	0.68	2.25
7-148-560	50	3/4	2.00	0.68	1.75
7-148-580	50	1	2.00	0.68	2.25
7-148-590	50	1 1/4	2.40	0.68	2.75
7-148-500	50	1 1/2	2.40	0.94	3.75
7-148-660	63	3/4	2.00	0.68	1.75
7-148-680	63	1	2.00	0.68	2.25
7-148-690	63	1 1/4	2.40	0.68	2.75
7-148-600	63	1 1/2	2.40	0.94	3.75
7-148-860	80	3/4	2.40	0.68	1.75
7-148-880	80	1	2.40	0.68	2.25
7-148-890	80	1 1/4	2.75	0.68	2.75
7-148-800	80	1 1/2	2.75	0.94	3.75
7-148-810	80	2	2.75	0.94	4.88
7-148-100	100	1 1/2	2.75	0.94	3.75
7-148-110	100	2	2.75	0.94	4.88

PSC POLYGONAL TAPER

■ ISO 26623-1

